



## Special order options for Leaded Aluminum Electrolytic Capacitors

### Axial Taping Suffixes

Axial taping	Suffix
All Axial lead Tape and Reel	SD
Axial taping and reel, Non-standard taping	SDC#

### Radial Taping Suffixes

Diameter	Taping configuration	Suffix
4,5,6.3,8,10,12.5	Ammo pack, 5.0 mm lead spacing	SA
4,5,6.3	Ammo pack, 2.5 mm lead spacing	ST
8	Ammo pack, 3.5 mm lead spacing (straight leads)	SJ
4	Ammo pack, 1.5 mm lead spacing (straight leads)	SA1L
5	Ammo pack, 2.0 mm lead spacing (straight leads)	SA2L
16,18	Ammo pack, 7.5 mm lead spacing (straight leads), 15mm feeder hole spacing	TA
12.5	Ammo pack, 5 mm lead spacing , 15mm feeder hole spacing	TH

### Cut and formed leads suffixes

Diameter	Description	Suffix
4, 5, 6.3, 8	Cut and formed leads	B
4, 5, 6.3, 8, 10, 12.5, 16, 18	Straight leads	CC
4, 5, 6.3, 8, 10, 12.5, 16, 18	Snap-in formed leads	SI

### Optional Sleeving Suffix

	Suffix
Polyester (PET) Sleeve	Y

### Special/Nonstandard tolerance Suffix

Suffix
K (+/- 10%)
Q (-10%, +30%)

### Optional end sealing Suffix

	Suffix
Epoxy end seal	PX
Epoxy end seal with Mylar sleeve	MX

Add the suffix to the end of the part number

