



## Special order options for Leaded Aluminum Electrolytic Capacitors

### Axial Taping Suffixes

Axial taping	Suffix
All Axial lead Tape and Reel	SD
Axial taping and reel, Non-standard taping	SDC#

### Radial Taping Suffixes

Diameter	Taping configuration	Suffix
4,5,6.3,8,10,12.5	Ammo pack, 5.0 mm lead spacing	SA
4,5,6.3	Ammo pack, 2.5 mm lead spacing	ST
8	Ammo pack, 3.5 mm lead spacing (straight leads)	SF
4	Ammo pack, 1.5 mm lead spacing (straight leads)	ST1
5	Ammo pack, 2.0 mm lead spacing (straight leads)	ST2
16,18	Ammo pack, 7.5 mm lead spacing (straight leads), 15mm feeder hole spacing	SQ
12.5	Ammo pack, 5 mm lead spacing , 15mm feeder hole spacing	SH

### Cut and formed leads suffixes

Diameter	Description	Suffix
4, 5, 6.3, 8	Cut and formed leads	B
4, 5, 6.3, 8, 10, 12.5, 16, 18	Straight leads	CC
4, 5, 6.3, 8, 10, 12.5, 16, 18	Snap-in formed leads	SI

### Optional Sleeving Suffix

	Suffix
Polyester (PET) Sleeve	Y

### Special/Nonstandard tolerance Suffix

Suffix
K (+/- 10%)
Q (-10%, +30%)

### Optional end sealing Suffix

OPTION	Suffix
Epoxy end seal	PX
Epoxy end seal with PET sleeve over PVC SLEEVE	MX
PET Sleeve over PVC only	MS

Add the suffix to the end of the part number

