



**333MPR400K**  
GENERAL PURPOSE FILM  
Parts are RoHS compliant

**ELECTRICAL SPECIFICATIONS**

Capacitance: 0.033 uF

Dissipation Factor: 0.001 Max at 1000 Hz and 25°C , 0.004 Max at 100 kHz and 25°C

Temperature Coefficient: -200 PPM/°C: -100 PPM/°C, 100 PPM/°C

Ripple Current: at and

ESR: 5.359 Ohms at 1 kHz and 20°C

Self Inductance: 1 Nanohenries maximum per mm of pitch

dvdt: 350 V/μs

Tolerance: -10 % , +10 %

Temperature Range: -55°C to +105°C

Above 85°C the rated (DC/AC) voltage must be derated at per 1.25%/2.25%/°C

WVDC: 400 Volts DC

SVDC: N/A Volts DC

VAC: 220 Volts AC

Terminal to Terminal Dielectric strength: 1.6 times the rated DC voltage when applied between the terminals for 2 seconds

Terminal to case Dielectric strength: 2 VAC when applied between the terminals and case for 2~5 seconds

Insulation Resistance (Terminal to Terminal): 30000 MINIMUM after 100 Volts DC is applied for 60 seconds at 20°C

Insulation resistance (Terminal to Case): N/A Megohms MINIMUM after 0 Volts DC is applied for 0 seconds at 0

Reliability: Load Life: 2000 hours at 85°C with 125% of rated voltage

Capacitance Change: ≤3% of initially measured value

D.F. Change: ≤125% of maximum specified value

I.R. Change: >50% of minimum specified value

**PHYSICAL DIMENSIONS**

Length (L): 13 mm, MAX mm

Height (H): 11 mm, +/-MAX mm

Thickness (T): 6.5 mm, +/-MAX mm

Lead Spacing (S): 10 mm, +/-1.5 mm

Lead Diameter (d): 0.6 mm, +/-0.05 mm

Lead Length (LL): 15mm, +/- MIN mm

