



806FSL360XCD

PHOTOFLASH ALUMINUM ELECTROLYTIC CAPACITORS

Parts are RoHS compliant

Date code when parts became RoHS: 1327

APPLICATIONS: Photoflash, strobes, Security systems

ELECTRICAL SPECIFICATIONS

Capacitance: 80 μ F

Dissipation Factor: 0.07 Max at 120 Hz and 20°C

Temperature Range: -20°C to +70°C

Impedance: N/A

Tolerance: -20 %, +50 %

WVDC: 360 Volts DC

SVDC: 390 Volts DC

Ripple Current: at and

Impedance Ratios: - and - -

Leakage Current: $3\sqrt{CV}$

509.12 μ A after 5 Minutes

Charge/discharge: 1000000 charge/discharge cycles at rated voltage & 5~35C repeating every 30 seconds thru a Xe tube having a discharge resistance of 0.7 to 1 Ohm

Capacitance Change: $\leq 10\%$ of initial measured value

Dissipation Factor: $\leq 150\%$ of maximum specified value

Leakage Current: $\leq 200\%$ of maximum specified value

Frequency Multipliers:

| 50 HZ | 120 HZ | 400 HZ | 1 KHZ | 10 KHZ | 100 KHZ |
|-------|--------|--------|-------|--------|---------|
| 1 | 1 | 1 | 1 | 1 | 1 |

Temperature Multipliers:

| 45°C | 60°C | 70°C | 65°C | 75°C | 85°C | 105°C | 125°C |
|------|------|------|------|------|------|-------|-------|
| 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 |

PHYSICAL DIMENSIONS

Diameter (D): 25 mm + 1 mm

Length (L): 30 mm + 2 mm


Lead Spacing (S): 10 mm +/- 1 mm

Coating: BlackPVC sleeving

Lead Wire Diameter (d): 4 mm +/- 0.5 mm

Lead Length: 5 mm +/- 1 mm

Lead Finish: Matte Tin



2400 East Devon Avenue Suite 292 Des Plaines, IL 60018 (847) 675-1760 FAX (847) 673-2850

Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, www.ilcap.com.hk

© Copyright 2020 Illinois Capacitor. An affiliate of Cornell Dubilier, All Rights Reserved