



## 474SML050MD4

SURFACE MOUNT

Parts are RoHS compliant

Date code when parts became RoHS: 26

**APPLICATIONS:** General purpose, filtering, bypass, filtering

### ELECTRICAL SPECIFICATIONS

**Capacitance:** 0.47 uF

**Dissipation Factor:** 0.12 Max at 120 Hz and 20°C

**Temperature Range:** -40°C to +85°C

**Impedance:** N/A

**Tolerance:** -20 %, +20 %

**WVDC:** 50 Volts DC

**SVDC:** 63 Volts DC

**Ripple Current:** 6.8 mA at 120 Hz and 85°C

**Impedance Ratios:**-25°C/20°C 2 and -40°C/20°C - 3

**Leakage Current:** .01CV or 3uA, whichever is greater  
3 uA after 2 Minutes

**Load Life:** 2000 hours at 85°C with 100 % of rated voltage and with 0 % of rated ripple current

**Capacitance Change:** ≤20% of initial measured value

**Dissipation Factor:** ≤200% of maximum specified value

**Leakage Current:** ≤100% of maximum specified value

#### Frequency Multipliers:

50 HZ	120 HZ	400 HZ	1 KHZ	10 KHZ	100 KHZ
0.7	1	1.17	1.36	1.5	1.5

#### Temperature Multipliers:

45°C	60°C	70°C	65°C	75°C	85°C	105°C	125°C
1.35	1.35	1.35	1.35	1	1	0	0

### PHYSICAL DIMENSIONS

**Diameter (D):** 4 mm + 0.5 mm


**Length (L):** 5.4 mm + 0.2 mm

**Lead Spacing (S):** 1 mm +/- 0.2 mm

**Lead Wire Diameter (d):** 0.65 mm +/- 0.15 mm

**Lead Length:** 3 mm +/- 0.2 mm

**Lead Finish:** Matte Tin



2400 East Devon Avenue Suite 292 Des Plaines, IL 60018 (847) 675-1760 FAX (847) 673-2850

Illinois Capacitor (HK) Ltd., Tel: 85227930931, Fax: 85227930731, [www.illcap.com.hk](http://www.illcap.com.hk)

© Copyright 2019 Illinois Capacitor. An affiliate of Cornell Dubilier. All Rights Reserved